

# TECHNICAL BULLETIN

 <b>CITY OF RALEIGH, N.C.</b>	<b>INSPECTIONS DEPARTMENT 2009 NCPC</b>			
<small>SUBJECT</small> <b>Protective Structures for Outside Drains</b> Municipal Code	<small>SECTION</small> <b>8-2113</b>	<small>PAGE</small> 	<small>EFFECTIVE DATE</small> <b>8/19/03</b>	<small>REVISION DATE</small> <b>12/3/09</b>
	<small>PREPARED BY</small> <b>DB, MB, GM, SL, JL</b>	<small>REVISED BY</small> <b>KP, WP</b>	<small>APPROVED BY</small> <b>FO</b>	

**City of Raleigh**

**Municipal Code Section 8-2113**

(13) Storm water, surface water, ground water, artesian well water, roof runoff, substitute drainage, swimming pool drainage, condensate, de-ionized water, noncontact cooling water and unpolluted industrial waste water shall not discharge to the sanitary sewer system, unless specifically authorized by the POTW Director (Public Utilities Director).

**Conclusion**

All drains connected to the sanitary system when exposed to stormwater must have a protective structure with a minimum of 3 sides and a roof protecting the drain. The structure must meet the requirements of the 2009 NC Building Code.